



Type	ELOPHY 23-5
Thrust Capacity (KG / N)	23 / 230
Thrust Stroke (MM)	50
Input Supply*	415V/3 ϕ / 50Hz
Oil Capacity (Ltr)**	2

Notes:

- Operating position of thruster must be within 10° of the vertical.
- Supply leads must be flexible and allow thruster to pivot.

*Thruster can also be supply with different voltage and frequency as per customer requirements.
 ** Oil should be use Transformer Oil BS 148.

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN MILLIMETERS
 SURFACE FINISH:
 TOLERANCES:
 LINEAR:
 ANGULAR:

FINISH:

DEBURR AND
 BREAK SHARP
 EDGES

DO NOT SCALE DRAWING

REVISION

Speedage Engineers (India) Pvt. Ltd.

NAME	SIGNATURE	DATE	CONTACT
DRAWN Himanshu Tiwari			
CHK'D			
APPV'D J.A. Raichandani			9810173991
MFG			
Q.A			

TITLE:

**ELOPHY THRUSTER
 JET-1**

DWG NO.

SAE/DWG/JET1/23-5/01

A4

THIS DRAWING IS THE PROPERTY OF **SPEEDAGE ENGINEERS (INDIA) PVT. LTD.** & MUST NEITHER BE COPIED NOR BE MADE KNOWN TO ANY OTHER PARTY WITHOUT THEIR PRIOR WRITTEN CONSENT.

MATERIAL:

WEIGHT:

SCALE: 1:3

SHEET 1 OF 1